



# 全漢企業股份有限公司

## 電氣規格書

版次 : 5  
文件編號 : ESD04021308  
附件版本 : 01  
研發部門 : RD1  
作者 : 黃銀山/jhon  
Model No/Type : AX500-A  
機密 : N  
發行日期 : 2004/9/13-13:48:13  
備註 : AX500-A  
升版理由 : 增加 9PA5000109



單位	姓名	單位	姓名	單位	姓名
安規 1	Chow 周懿慧	產品工程 1	Jhon 黃銀山	主管	Phc 陳炳旭

相關料號：

9PA5000100 PILOT

RUN,AX500-A,PC,ATX,S,W/NK,W/IO,WO/O,W/SS,FSP,W/PFC(P),4L1S,STD,INTEL,WO/AUTO,RD1

9PA5000101

,AX500-A,(RMB1),PC,ATX,S,W/NK,W/IO,WO/O,W/SS,FSP,W/PFC(P),8L1S,INTEL,WO/AUTO,9PA5000100,RM,RD1

9PA5000102

,AX500-A,(S281),PC,ATX,S,W/NK,W/IO,WO/O,W/SS,FSP,W/PFC(P),8L1S,INTEL,WO/AUTO,9PA5000101,RM,RD1

9PA5000103

,AX500-A,(A551),PC,ATX,S,W/NK,W/IO,WO/O,W/SS,FSP,W/PFC(P),8L1S,INTEL,WO/AUTO,9PA5000101,RM,RD1

9PA5000104

,AX500-A,(F061),PC,ATX,S,W/NK,W/IO,WO/O,W/SS,FSP,W/PFC(P),8L1S,INTEL,WO/AUTO,9PA5000101,RM,RD1

9PA5000105

,AX500-A,(C241),PC,ATX,S,W/NK,W/IO,WO/O,W/SS,FSP,W/PFC(P),8L1S,INTEL,WO/AUTO,9PA5000101,RM,RD1

9PA5000106

,AX500-A,(F221),PC,ATX,S,W/NK,W/IO,WO/O,W/SS,FSP,W/PFC(P),8L1S,INTEL,WO/AUTO,9PA5000101,RM,RD1

9PA5000107

,AX500-A,(F181),PC,ATX,S,W/NK,W/IO,WO/O,W/SS,FORTUNE  
TEC,W/PFC(P),8L1S,INTEL,WO/AUTO,9PA5000101,RM,RD1

9PA5000108

,AX500-A,(RMB2),PC,ATX,S,W/NK,W/IO,WO/O,W/SS,AMACROX,W/PFC(P),8L1S,OEM,  
INTEL,WO/AUTO,9PA5000100,RM,RD1

9PA5000109

AX500-A,(F222),PC,ATX,S,W/NK,W/IO,WO/O,W/SS,FSP,W/PFC(P),8L1S,OEM,INTEL,  
WO/AUTO

台灣 桃園市建國東路 22 號

No. 22, Jianguo E. Rd., Taoyuan City, Taiwan, R.O.C.

TEL : +886-3-375-9888 FAX : +886-3-375-6966



全漢企業股份有限公司

台灣 桃園市建國東路 22 號

SPI Electronic Co. Ltd.

No. 22, Jianguo E. Rd., Taoyuan City, Taiwan, R. O. C

TEL: +886-3-375-9888

FAX: +886-3-375-6966

# SPECIFICATION

## xX500-A

### (x=A-Z)

DATE: APR,02, 2004

REV : 1

表單編號 : 7000P-0105



## 1.0 GENERAL REQUIREMENTS

This specification describes a 460 watts power supply.  
 With+ 5V stand-by , remote ON/OFF control for ATX system .

## 2.0 INPUT REQUIREMENTS

The power supply shall operate in 115Vrms±10% or 230Vrms±10%.  
 The power supply shall operate from an AC mains frequency of 47 through 63 Hz.  
 The Ac mains single-cycle peak inrush current shall be limited to 90 amps cold, 120 amps warm measured at 264 Vrms, 50 Hz and coinciding with the AC main voltage peak.  
 The AC mains steady-state RMS input current shall be:  
 10 amps maximum / 115 Vrms, 60 Hz.  
 5 amps maximum / 230 Vrms, 50 Hz.

## 3.0 OUTPUT REQUIREMENTS

### 3.1 OUTPUT VOLTAGE AND CURRENT

	MINIMUM LOAD	NORMAL LOAD	MAXIMUM LOAD	LOAD REG.	LINE REG.	RIPPLE & NOISE
+3.3V	0.5A	15.0A	30A	± 5%	± 1%	50mV P-P
+5V	1.0A	14.0A	28A	± 5%	± 1%	50mV P-P
+12V1DC	1.0A	7.0A	15A	± 5%	± 1%	120mV P-P
+12V2DC	1.0A	8.5A	15A	± 5%	± 1%	120mV P-P
-12V	0.0A	0.4A	0.5A	± 10%	± 2%	120mV P-P
+5Vsb	0.0A	1.0A	2.0A	± 5%	± 1%	50mV P-P

- (1). +3.3V &+5V total output not exceed 160W.  
 When +3.3V is load to 30A,the +5V maximum load is 12.0A.  
 When +3.3V is load to 6.0A,the +5V maximum load is 28A.
- (2) . +3.3V &+5V & +12V1DC & +12V2DC total output not exceed 445W
- (3) All outputs shall be safety-isolated from the AC mains and share a common return. This common return must be connected to supply chassis.
- (4) Voltages and ripple are measured at the load side of mating connectors with a 0.1 uF monolithic ceramic capacitor paralleled by a 10 uF electrolytic capacitor across the measuring terminals.

## LOAD REGULATION CHARACTERISTICS

NO.	LOAD CONDITION	OUTPUT LOAD					
		+3.3V	+5V	+12V1DC	+12V2DC	-12V	+5Vsb
1	COND.1	10A	10A	15.0A	15.0A	0.5A	2.0A
2	COND.2	3.0A	28A	10.0A	10.0A	0.5 A	1.0A
3	COND.3	0.5A	6.2A	15.0A	15.0A	05A	2.0A
4	COND.4	30A	2.0A	1.0A	1.0A	0.1A	1.5A
5	COND.5	0.5A	1.0A	1.0A	1.0A	0A	0A
6	COND.6	13A	15A	4.0A	4.0A	0.25A	1.0A
7	COND.7	0.5A	15A	4.0A	4.0A	0.25A	0.5A
8	COND.8	0.5A	5A	8.0A	8.0A	0.5A	2.0A
9	COND.9	20A	16.8A	13.0A	12.0	0.5A	2.0A

### 3.2 REMOTE ON/OFF CONTROL

The power supply shall accept a logic open collector level which will disable

/ enable all the output voltage (exclude + 5V standby ).

As logic level is low, outputs voltage were enable.

As logic level is high, outputs voltage were disable.

Note: 1. Logic high level :3.50-5.25V while sourcing 0.4mA maximum.

2. Logic low level : 0-0.5V while sinking 1.5mA maximum.

3. Rise Time : 2ms maximum (10%-90%).

### 3.3 OUTPUT VOLTAGE HOLD-UP TIME

16.6 mS minimum : at 115V / 60 Hz.

12.0 mS minimum : at 230V / 50 Hz.

### 3.4 OPERATION AT NO LOAD

The power supply shall be capable of being operated with no load on any or all outputs without damage. For no load on +3.3V&+5V, the output shall not exceed +4.5 & +6.5Vdc and the power supply may shutdown and require by remote-control or remove AC power restart.

### 3.5 PROTECTION

#### 3.5.1 OVER-VOLTAGE PROTECTION

In the event of an over-voltage condition on +3.3 & +5Vdc &+12V the power supply shall shutdown and require remote control or remove the AC mains input to reset the system.

+5V : 6.5V(maximum)

+3.3V : 4.6V(maximum)

+12V1DC : 15.5V(maximum)

+12V2DC : 15.5V(maximum))

### 3.5.2 OVER-CURRENT PROTECTION

There shall be protection from an output over-current event. The supply may shutdown from such an event and require power-on restart. Testing consists of application of the listed over-current value with maximum load on all other outputs.

Over-current test values: (maximum load)

+3.3V	:	80maximum
+5V	:	48maximum
+12V1DC	:	20maximum
+12V2DC	:	20maximum

### 3.5.3 SHORT-CURRENT PROTECTION

A short circuit at any output shall cause no damage to the power supply nor blow the primary fuse. The supply may shut down in the event of a short circuit and require power-on restart. A short circuit consists of application of a test resistance of less than 0.05 ohms at each output with maximum load on all outputs.

## 3.6 OUTPUT RISE TIME

The cold-start enable output voltage risetime of all outputs shall be measured with maximum load on all outputs.

risetime :	+3.3V	20mS (maximum)
(10-95%)	+5V	20mS (maximum)
	+12 V1DC	20mS (maximum)
	+12 V2DC	20mS (maximum)
	-12 V	20mS (maximum)
	+5Vsb	20mS (maximum)

## 3.7 OUTPUT OVERSHOOT

No output voltage shall overshoot or generate spikes at turn-on or turn-off, during momentary power loss, output short, or realistic input voltage or output load changes, Overshoot is defined as any output that exceeds the voltage tolerance plus or minus an additional 5%.

## 3.8 EFFICIENCY

Overall efficiency must be 70% minimum measured at normal AC mains voltage and frequency with maximum loads on all outputs.

## 3.9 POWER GOOD SIGNAL

115V (FULL LOAD) : 100-500mS  
 230V (FULL LOAD) : 100-500mS

### 3.10 POWER FAIL SIGNAL

115V (FULL LOAD) : 1mS minimum.

230V (FULL LOAD) : 1mS minimum.

### 3.11 POWER ON TIME

115V(FULL LOAD) : 500mS maximum.

230V(FULL LOAD) : 500mS maximum.




Figure 1

- T2 : RISE TIME < 20mS
- T3 : POWER GOOD DELAY TIME 100mS-500mS
- T4 : POWER FAIL DELAY TIME > 1mS
- T5 : POWER GOOD RISE TIME ≤ 10mS

## 4.0 PHYSICAL ENVIRONMENT

### 4.1 OPERATING CONDITIONS

The power supply shall be capable of continuous operation and meet all electrical specification without need for adjustment when subjected to the following environmental conditions:

4.1.1 AMBIENT TEMPERATURE : 0 TO 50°C

The maximum continuous power rating of supply is 460W at 25 °C .De-rate 2.5W/ °C from 50 °C to 25 °C .

4.1.2 RELATIVE HUMIDITY : 90%

## 4.2 STORAGE AND SHIPPING CONDITIONS

No degradation of the power supply shall occur during shipping or storage at the specified conditions.

4.2.1 AMBIENT TEMPERATURE : -20 TO +65 °C

4.2.2 RELATIVE HUMIDITY : 95%

## 4.3 SHOCK AND VIBRATION

The power supply will withstand the following imposed conditions without experiencing non-recoverable failure or deviation from specified output characteristics.

Storage -40G,11mSec. half-sine wave pulse in both directions on three mutually perpendicular axes.

Operating -10G, 11mSec. half-sine wave pulse in both directions on three mutually perpendicular axes.

Vibration Operation-Sine wave excited, 0.25G maximum acceleration. 10-250 Hz, swept at one octave/min. Fifteen minute dwell at all resonant points, where resonance is defined as those exciting frequencies at which the device under test experiences excursions two times large than non-resonant excursions.

## 5.0 REGULATORY COMPLIANCE

### 5.1 SAFETY REQUIREMENTS

-CE

-TUV EN60950

-UL 60950

-CSA

-NEMKO + CB REPORT

### 5.2 DIELECTRIC STRENGTH

Primary to Frame Ground : 1800 Vac for 1 sec.

Primary to Secondary : 1800 Vac for 1 sec.

### 5.3 INSULATION RESISTANCE

Primary to Secondary : 20 Meg. ohms Minimum.

Primary to FRAME GROUND : 20 Meg. ohms Minimum.

## 5.4 GROUND LEAKAGE CURRENT

The power supply ground leakage current shall be less than 3.5mA.

## 5.5 EMISSION REQUIREMENTS

When testing the power supply must operate within the listed requirements.

# 6.0 OTHER REQUIREMENTS

## 6.1 COOLING

With the fan voltage set to around 12 volts,  
the fan will deliver greater than 38.2 CFM with the power  
supply in open air.

## 6.2 INPUT CONNECTIONS

Refer to Mechanical Specifications for placement.

The AC mains input are through a three-circuit IEC type connector mounted  
on the rear of the power supply chassis.

## 6.3 RELIABILITY

The power supply reliability, when calculated by MIL-HDBK-217; latest  
revision, are exceed 100,000 hours with all output at maximum load and an  
ambient temperature of 25°C.

## 7.0 Revision History:

Rev	Description	Date