



IPC

1U/2U

FLEX

REDUNDANT

AT/ATX

POWER
NEVER ENDS

About FSP

FSP, a leading power supply manufacturer with more than 20 years dedicated in power industry. Strong RD resource is one of our advantages, 15 RD centers and more than 500 professional engineers providing high reliability, high efficiency designed products in order to meet various demands. Providing clean and high efficiency products is always one of our goals, all products from FSP are in compliance with latest safety and efficiency request worldwide.

Established : April, 1993

Equity : US\$ 210 million

Headquarters : Taiwan, Taoyuan

Quality Certification : ISO 9001, ISO 14001, OHSAS 18001,
QC 080000, ISO 14064-1, EICC

Listed on Taiwan Stock Exchange in 2002

Global Service Locations : 29 Sales offices/ 7 Manufacturers/ 15 R&D Centers

REDUNDANT Specifications

| Model No. | Wattage | Dimension L x W x H (mm) | 80 Plus Efficiency Level | PMBus | Output Voltage [Output Current: Min ~Max (A)] PEAK (A) | | | | | | | |
|------------------|---------|--------------------------------|--------------------------------|-------|--|--------|------------------------|--------|--------|-------|-------|--------|
| | | | | | 3.3V | 5V | 12V1 | 12V2 | 12V3 | -12V | 5Vsb | -5V |
| FSP350-80EVMR | 350 | 190 x 150 x 84 | | | 0.5~20 | 0.5~20 | 0.5~18 | 0.5~18 | 0.5~14 | 0~0.8 | 0~2 | 0~0.5 |
| FSP500-80EVMR | 500 | 190 x 150 x 84 | Standard | | 0.5~20 | 0.5~20 | 0.5~19 | 0.5~19 | 0.5~18 | 0~0.8 | 0~2 | 0~0.5 |
| ◎FSP350-50MRA(S) | 350 | 190 x 150 x 84 | Gold | V1.2 | 0~20 | 0~20 | 1~29 | | | 0~0.5 | 0~2 | 0~0.3▲ |
| FSP500-60MRA(S) | 500 | 190 x 150 x 84 | Gold | V1.2 | 0.1~20 | 0.1~20 | 1~40 | | | 0~0.5 | 0~3 | 0~0.3▲ |
| FSP600-60MRA(S) | 600 | 190 x 150 x 84 | Gold | V1.2 | 0.1~20 | 0.1~20 | 1~49 | | | 0~0.5 | 0~3 | 0~0.3▲ |
| ★FSP250-60RGHBA | 250 | 260 x 106 x 41.3 | Gold | | 0~19 | 0~17 | 0.5~14 | 0.5~14 | | 0~0.5 | 0~2 | |
| ★FSP300-60RGHBA | 300 | 260 x 106 x 41.3 | Gold | | 0~20 | 0~20 | 0.5~14 | 0.5~14 | | 0~0.5 | 0~2 | |
| ★FSP400-60RGHBB1 | 400 | 190 x 150 X 86 | Platinum | V1.2 | 0~20 | 0~20 | 0~16 | 0~16 | | 0~0.5 | 0~3 | |
| ★FSP500-70RGHBB1 | 500 | 190 x 150 X 86 | Platinum | V1.2 | 0~20 | 0~20 | 0~16 | 0~16 | 0~16 | 0~0.5 | 0~3 | |
| ◎FSP550-50ERS | 550 | 250 x 76 x 84 | Platinum | V1.2 | 0~20 | 0~20 | 0.5~43 | | | 0~0.3 | 0~4 | |
| ◎FSP600-50ERS | 600 | 250 x 76 x 84 | Platinum | V1.2 | 0~20 | 0~20 | 0.5~48 | | | 0~0.3 | 0~4 | |
| FSP700-50DRS | 700 | 250 x 76 x 84 | Gold | V1.2 | 0~25 | 0~25 | 0.5~56 | | | 0~0.3 | 0~4.5 | |
| ★FSP700-50ERS | 700 | 250 x 76 x 84 | Platinum | V1.2 | 0~25 | 0~25 | 0.5~56 | | | 0~0.3 | 0~4.5 | |
| FSP800-50DRS | 800 | 250 x 76 x 84 | Gold | V1.2 | 0~25 | 0~25 | 0.5~65 | | | 0~0.3 | 0~4.5 | |
| ★FSP800-50ERS | 800 | 250 x 76 x 84 | Platinum | V1.2 | 0~25 | 0~25 | 0.5~64 | | | 0~0.3 | 0~4.5 | |
| ◎FSP1200-50DRS | 1200 | 330 x 76 x 84 | Platinum | V1.2 | 0~30 | 0~30 | 0.5~73 (90~140Vrms) | | | 0~0.3 | 0~5 | |
| | | | | | | | 0.5~97.5 (180~264Vrms) | | | | | |
| ◎FSP1400-50DRS | 1400 | 330 x 76 x 84 | Platinum | V1.2 | 0~30 | 0~30 | 0.5~73 (90~140Vrms) | | | 0~0.3 | 0~5 | |
| | | | | | | | 0.5~115 (180~264Vrms) | | | | | |

Remark: ★ : Coming Soon Product ; ◎ : New Product ; ▲ : Optional

1U Specifications

| Model No. | Wattage | Dimension L x W x H (mm) | 80 Plus Efficiency Level | PMBus | Output Voltage [Output Current: Min ~Max (A)] PEAK (A) | | | | | | | | |
|----------------|---------|--------------------------------|--------------------------------|-------|--|--------|--------|--------|--------|--------|----------|-------|-------|
| | | | | | 3.3V | 5V | 12V1 | 12V2 | 12V3 | 12V4 | -12V | 5Vsb | -5V |
| FSP250-701UH | 250 | 190 x 100 x 40.5 | Standard | | 0.5~16 | 0.5~18 | 1~16 | 1~16 | | | 0~0.8 | 0~2.5 | 0~0.3 |
| FSP250-701UJ | 250 | 190 x 100 x 40.5 | Bronze | | 0.3~14 | 0.3~16 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | 0~0.3 |
| FSP250-701US | 250 | 190 x 100 x 40.5 | Gold | | 0.3~14 | 0.3~16 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | 0~0.2 |
| FSP300-701UH | 300 | 190 x 100 x 40.5 | Standard | | 0.5~16 | 0.5~18 | 1~16 | 1~16 | | | 0~0.8 | 0~2.5 | 0~0.3 |
| FSP300-701UJ | 300 | 190 x 100 x 40.5 | Bronze | | 0.3~14 | 0.3~16 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | 0~0.3 |
| FSP300-701US | 300 | 190 x 100 x 40.5 | Gold | | 0.3~14 | 0.3~16 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | 0~0.2 |
| ◎FSP300-60UAP | 300 | 190 x 100 x 40.5 | Platinum | | 0.3~14 | 0.3~16 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | |
| FSP350-701UH | 350 | 190 x 100 x 40.5 | Standard | | 0.5~16 | 0.5~18 | 1~16 | 1~16 | | | 0~0.8 | 0~2.5 | 0~0.3 |
| FSP350-701UJ | 350 | 190 x 100 x 40.5 | Bronze | | 0.3~16 | 0.3~18 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | 0~0.3 |
| FSP350-701US | 350 | 190 x 100 x 40.5 | Gold | | 0.3~16 | 0.3~16 | 0.5~18 | 0.5~18 | | | 0~0.5 | 0~3 | 0~0.2 |
| ◎FSP350-60UAP | 350 | 190 x 100 x 40.5 | Platinum | | 0.3~14 | 0.3~16 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | |
| FSP400-701UH | 400 | 220 x 100 x 40.5 | Bronze | | 0.5~20 | 1~20 | 0.5~16 | 1~16 | 1~16 | | 0~0.5 | 0~3 | |
| FSP400-701US | 400 | 220 x 100 x 40.5 | Gold | | 0.3~16 | 0.3~16 | 0.5~18 | 0.5~18 | | | 0~0.5 | 0~3 | 0~0.2 |
| ◎FSP400-60UAP | 400 | 220 x 100 x 40.5 | Platinum | | 0.3~16 | 0.3~18 | 0.5~18 | 0.5~18 | | | 0~0.5 | 0~3 | |
| ◎FSP400-70UDPB | 400 | 220 x 100 x 40.5 | Platinum | V1.2 | 0.3~16 | 1~18 | 0.5~16 | 1~16 | 1~16 | | 0~0.5 | 0~3 | |
| FSP460-701UH | 460 | 220 x 100 x 40.5 | Bronze | | 0.5~20 | 1~20 | 0.5~16 | 1~16 | 1~16 | | 0~0.5 | 0~3 | |
| FSP500-701UH | 500 | 220 x 100 x 40.5 | Bronze | | 0.5~20 | 1~20 | 0.5~16 | 1~16 | 1~16 | | 0~0.5 | 0~3 | |
| FSP500-701UN | 500 | 220 x 100 x 40.5 | Gold | | 0.1~20 | 0.1~20 | 0.5~16 | 0.5~16 | 0.5~16 | | 0~0.5 | 0~3.5 | |
| FSP500-701UP | 500 | 220 x 100 x 40.5 | Gold | V1.2 | 0.1~20 | 0.1~20 | 0.5~16 | 0.5~16 | 0.5~16 | | 0~0.5 | 0~3.5 | |
| ◎FSP500-70UDPB | 500 | 220 x 100 x 40.5 | Platinum | V1.2 | 0.1~20 | 0.5~20 | 1~16 | 1~16 | 0.5~16 | | 0~0.5 | 0~3 | |
| FSP600-801UK | 600 | 250 x 100 x 40.5 | Bronze | | 0.5~24 | 0.5~24 | 0.5~16 | 0.5~16 | 0.5~16 | 0.5~16 | 0.05~0.5 | 0.1~4 | |
| ★FSP600-80UEPB | 600 | 240 x 100 x 40.5 | Platinum | V1.2 | 0.1~25 | 1~25 | 1~16 | 1~16 | 1~16 | 1~16 | 0~0.5 | 0~4 | |
| FSP700-801UK | 700 | 250 x 100 x 40.5 | Bronze | | 0.5~24 | 0.5~30 | 0.5~16 | 0.5~16 | 0.5~16 | 0.5~16 | 0.05~0.5 | 0.1~4 | |
| ★FSP700-80UEPB | 700 | 240 X 100 X 40.5 | Platinum | V1.2 | 0.1 ~ 25 | 1~30 | 1~16 | 1~16 | 1~16 | 1~16 | 0~0.5 | 0~4 | |

Remark: ★ : Coming Soon Product ; ◎ : New Product

AT / ATX Specifications

| Model No. | Wattage | Dimension L x W x H (mm) | 80 Plus Efficiency Level | PMBus | Output Voltage [Output Current: Min ~Max (A)] PEAK (A) | | | | | | | | |
|----------------|---------|--------------------------------|--------------------------------|-------|--|--------|---------|------------------|------|------|-------|--------------|--------------|
| | | | | | 3.3V | 5V | 12V1 | 12V2 | 12V3 | 12V4 | -12V | 5Vsb | -5V |
| FSP300-40PFB | 300 | 140 x 150 x 86 | | | | 2~40 | 1~15 | | | | 0~0.8 | | 0~0.3 |
| FSP400-40PFB | 400 | 140 x 150 x 86 | | | | 2~42 | 1~15 | | | | 0~0.8 | | 0~0.3 |
| FSP250-70PFL | 250 | 140 x 150 x 86 | Bronze | | 0.3~14 | 0.5~14 | 0.5~17 | 0.5~17 | | | 0~0.5 | 0.1~3 3.5 | 0~0.3 |
| FSP300-70PFL | 300 | 140 x 150 x 86 | Bronze | | 0.3~19 | 0.5~16 | 0.5~17 | 0.5~17 | | | 0~0.5 | 0.1~3 3.5 | 0~0.3 0.2~5▲ |
| FSP350-70PFL | 350 | 140 x 150 x 86 | Bronze | | 0.1~15 | 0.2~15 | 0.1~16 | 0.5~17 | | | 0~0.5 | 0.1~3 3.5 | |
| FSP400-70PFL | 400 | 140 x 150 x 86 | Bronze | | 0.5~21 | 0.5~16 | 0.5~17 | | | | 0~0.5 | 0.1~3 3.5 | 0~0.3 0.2~5▲ |
| FSP460-70PFL | 460 | 140 x 150 x 86 | Bronze | | 0.5~22 | 0.5~16 | 0.5~18 | 0.5~18 | | | 0~0.5 | 0.1~3 3.5 | 0~0.3 0.2~5▲ |
| FSP500-60PFH | 500 | 140 x 150 x 86 | Sliver | | 0.1~24 | 0.2~20 | 0.1~16 | 0.5~18 0.5~16 | | | 0~0.5 | 0~3 3.5 | |
| ◎FSP500-70AAPB | 500 | 140 x 150 x 86 | Platinum | | 0.3~24 | 0.3~20 | 0.3~18 | 0.3~18 | | | 0~0.5 | 0~3 | 0~0.2 |
| FSP550-60PFH | 550 | 140 x 150 x 86 | Sliver | | 0.1~24 | 0.2~20 | 0.1~16 | 0.5~16 | | | 0~0.5 | 0~3 3.5 | |
| FSP600-80PSA | 600 | 140 x 150 x 86 | Bronze | | 1.5~25 | 1~25 | 1~16 | 1~16 | | | 0~0.5 | 0.1~4 | |
| FSP700-80PSA | 700 | 140 x 150 x 86 | Bronze | | 1.5~25 | 1~30 | 1~16 | 1~16 | | | 0~0.5 | 0.1~4 | |
| ◎FSP850-50AAG | 850 | 190 x 150 x 86 | Gold | | 0~25 | 0.1~25 | 0.2~70 | | | | 0~3.5 | | |
| ◎FSP1000-50AAG | 1000 | 190 x 150 x 86 | Gold | | 0~30 | 0.1~30 | 0.2~83 | | | | 0~4 | | |
| ◎FSP1200-50AAG | 1200 | 190 x 150 x 86 | Gold | | 0~30 | 0.1~30 | 0.2~100 | | | | 0~4 | | |

Remark: ★ : Coming Soon Product ; ◎ : New Product ; ▲ : Optional

2U Specifications

| Model No. | Wattage | Dimension L x W x H (mm) | 80 Plus Efficiency Level | PMBus | Output Voltage [Output Current: Min ~Max (A)] PEAK (A) | | | | | | | | |
|----------------|---------|--------------------------------|--------------------------------|-------|--|--------|--------|--------|--------|--------|----------|-------|-------|
| | | | | | 3.3V | 5V | 12V1 | 12V2 | 12V3 | 12V4 | -12V | 5Vsb | -5V |
| FSP300-702UJ | 300 | 200 X 100 X 70 | Bronze | | 0.3~16 | 0.3~16 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | 0~0.3 |
| FSP300-702US | 300 | 200 X 100 X 70 | Gold | | 0.3~14 | 0.3~16 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | 0~0.2 |
| ©FSP300-60WAP | 300 | 200 X 100 X 70 | Platinum | V1.2 | 0.3~14 | 0.3~16 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | |
| FSP400-702UJ | 400 | 200 X 100 X 70 | Bronze | | 0.3~18 | 0.3~20 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | 0~0.3 |
| FSP400-602UC | 400 | 240 X 100 X 70 | Standard | | 0.5~20 | 0.5~20 | 1.5~16 | 1.5~16 | | | 0~0.5 | 0~2.5 | |
| FSP400-702US | 400 | 200 X 100 X 70 | Gold | | 0.3~16 | 0.3~16 | 0.5~18 | 0.5~18 | | | 0~0.5 | 0~3 | 0~0.2 |
| ©FSP400-60WAP | 400 | 200 X 100 X 70 | Platinum | V1.2 | 0.3~16 | 0.3~18 | 0.5~18 | 0.5~18 | | | 0~0.5 | 0~3 | |
| FSP500-702UC | 500 | 240 X 100 X 70 | Standard | | 0.5~24 | 0.5~20 | 1~15 | 1~15 | 1~15 | | 0~0.5 | 0~2.5 | |
| FSP500-702UH | 500 | 240 X 100 X 70 | Bronze | | 0.5~20 | 1~20 | 0.5~16 | 1~16 | 1~16 | | 0~0.5 | 0~3 | |
| FSP500-702UN | 500 | 240 X 100 X 70 | Gold | | 0.1~20 | 0.1~20 | 0.5~16 | 0.5~16 | 0.5~16 | | 0~0.5 | 0~3.5 | |
| FSP500-702UP | 500 | 260 X 100 X 70 | Gold | V1.2 | 0.1~20 | 0.1~20 | 0.5~16 | 0.5~16 | 0.5~16 | | 0~0.5 | 0~3.5 | |
| FSP600-702UH | 600 | 240 X 100 X 70 | Bronze | | 1.5~25 | 1~25 | 1~16 | 1~16 | 1~16 | | 0~0.5 | 0~3 | |
| FSP600-802UQ | 600 | 240 X 100 X 70 | Gold | | 0.1~25 | 1~25 | 1~16 | 1~16 | 1~16 | 1~16 | 0~0.5 | 0~4 | |
| ★FSP600-80WEPB | 600 | 240 X 100 X 70 | Platinum | V1.2 | 0.1~25 | 1~25 | 1~16 | 1~16 | 1~16 | 1~16 | 0~0.5 | 0~4 | |
| FSP700-802UK | 700 | 240 X 100 X 70 | Bronze | | 0.5~24 | 0.5~30 | 0.5~16 | 0.5~16 | 0.5~16 | 0.5~16 | 0.05~0.5 | 0.1~4 | |
| FSP700-802UQ | 700 | 240 X 100 X 70 | Gold | | 0.1~25 | 1~30 | 1~16 | 1~16 | 1~16 | 1~16 | 0~0.5 | 0~4 | |
| ★FSP700-80WEPB | 700 | 240 X 100 X 70 | Platinum | V1.2 | 0.1~25 | 1~30 | 1~16 | 1~16 | 1~16 | 1~16 | 0~0.5 | 0~4 | |
| FSP750-802UQ | 750 | 240 X 100 X 70 | Gold | | 0.1~30 | 1~30 | 1~16 | 1~16 | 1~16 | 1~16 | 0~0.5 | 0~4 | |

Remark: ★ : Coming Soon Product ; © : New Product

FLEX Specifications

| Model No. | Wattage | Dimension L x W x H (mm) | 80 Plus Efficiency Level | PMBus | Output Voltage [Output Current: Min ~Max (A)] PEAK (A) | | | | | | | | |
|-----------------------|---------|--------------------------------|--------------------------------|-------|--|--------|---------------------|--------|------|------|----------|-------|-------------------------------------|
| | | | | | 3.3V | 5V | 12V1 | 12V2 | 12V3 | -12V | 5Vsb | -5V | 24V |
| FSP100-50LG | 100 | 150 x 81.5 x 40.5 | | | 0.3~6 | 0.3~8 | 1~4 | | | | 0~0.3 | 0~2 | |
| FSP150-50LG | | 150 x 81.5 x 40.5 | | | 0.3~10 | 0.3~13 | 1~10 | | | | 0.05~0.3 | 0~2 | |
| FSP150-50LH | 150 | 150 x 81.5 x 40.5 | Sliver | | 0.1~10 | 0.2~14 | 0.6~10 | | | | 0~0.3 | 0~2.5 | |
| FSP180-50LG | 180 | 150 x 81.5 x 40.5 | | | 0.3~14 | 0.3~16 | 1~14 | | | | 0~0.3 | 0~2 | |
| FSP180-50LH | 180 | 150 x 81.5 x 40.5 | | | 0.1~10 | 0.2~14 | 0.6~10 | | | | 0~0.3 | 0~2.5 | |
| FSP200-50LG | 200 | 150 x 81.5 x 40.5 | Sliver | | 0.3~14 | 0.3~16 | 1~14 | | | | 0~0.5 | 0~2 | |
| FSP220-50LH | 220 | 150 x 81.5 x 40.5 | Sliver | | 0.1~10 | 0.2~14 | 0.6~14 16 | | | | 0~0.3 | 0~2.5 | |
| ★FSP220-20FGGBD (POE) | 220 | 150 x 81.5 x 40.5 | Bronze | | | | 0~7 | | | | | | 2.5 |
| FSP250-60LG | 250 | 150 x 81.5 x 40.5 | Bronze | | 0.5~14 | 0.5~16 | 0.5~15 | 0.5~15 | | | 0.05~0.3 | 0~3 | |
| ©FSP250-60FAG | 250 | 150 x 81.5 x 40.5 | Gold | | 0.3~14 | 0.3~16 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | |
| ©FSP250-20FGGBC | 250 | 150 x 81.5 x 40.5 | Gold | | | | 0~20 | | | | 0~3 | | |
| ★FSP250-20FGGBD (POE) | 250 | 150 x 81.5 x 40.5 | Bronze | | | | 0~7.5 | | | | | | 3 |
| FSP280-60LB (24V) | 280 | 190 x 81.5 x 40.5 | | | 0.5~5 | 0.3~16 | 1~12 18A (500ms) | | | | 0~0.4 | 0~2.5 | 0.1~2.3 7A (20ms), 10.5A (1s) |
| ★FSP280-20FGGBD (POE) | 280 | 150 x 81.5 x 40.5 | Bronze | | | | 0~8 | | | | | | 3.4 |
| FSP300-60LG | 300 | 150 x 81.5 x 40.5 | Bronze | | 0.5~16 | 0.5~18 | 0.5~15 | 0.5~15 | | | 0~0.5 | 0~3 | |
| ©FSP300-60FAG | 300 | 150 x 81.5 x 40.5 | Gold | | 0.3~14 | 0.3~16 | 0.5~16 | 0.5~16 | | | 0~0.5 | 0~3 | |
| ©FSP300-20FGGBC | 300 | 150 x 81.5 x 40.5 | Gold | | | | 0~24 | | | | 0~3 | 0~0.2 | |
| FSP350-70LQ | 350 | 190 x 81.5 x 40.5 | Gold | | 0.3~16 | 0.3~16 | 0.5~18 | 0.5~18 | | | 0~0.5 | 0~3 | 0~0.2 |
| FSP400-70LQ | 400 | 190 x 81.5 x 40.5 | Gold | | 0.3~16 | 0.3~16 | 0.5~18 | 0.5~18 | | | 0~0.5 | 0~3 | |
| ©FSP400-20FBGB | 400 | 190 x 81.5 x 40.5 | Gold | | | | 0~32.1 | | | | 0~3 | | |
| ©FSP400-60FGGBA | 400 | 150 x 81.5 x 40.5 | Gold | | 0.1~14 | 0.1~16 | 0.1~18 | 0.2~18 | | | 0~0.5 | 0~3 | |

Remark: ★ : Coming Soon Product ; © : New Product

SFX Specifications

| Model No. | Wattage | Dimension L x W x H (mm) | 80 Plus Efficiency Level | PMBus | Output Voltage [Output Current: Min ~Max (A)] PEAK (A) | | | | | | | | |
|--------------|---------|--------------------------------|--------------------------------|-------|--|--------|------|------|------|------|-------|-------|-------|
| | | | | | 3.3V | 5V | 12V1 | 12V2 | 12V3 | -12V | 5Vsb | -5V | |
| FSP200-60PLC | 200 | 100 x 125 x 86 | | | 0.3~12 | 0.5~14 | 1~14 | | | | 0~0.3 | 0~2.5 | 0~0.2 |
| FSP250-60PLC | 250 | 100 x 125 x 86 | Bronze | | 0.3~12 | 0.5~17 | 1~18 | | | | 0~0.3 | 0~2.5 | 0~0.2 |

Product Advantages and Applications

Redundant



- 80 Plus Platinum & Gold certified efficiency
- Support PMBus v1.2
- Rapid hot-swappable and remarkable power density (up to 30.8 W/in³)
- Well working performance at 50°C (24 hours running)
- Operating altitude complies with CCC 5Km certification
- Common safety for CB, CE, TUV, UL, FCC, and CCC

Applications: For standard, advanced rack servers (including micro servers, cloud servers, embedded servers..etc) and storage systems.

Flex



- Widely input range from 90 to 264 VAC
- Low ripple & noise
- MTBF:100K hours at 25°C, and well working performance at 50°C
- Support OTP, OVP and OCP circuit protection
- Common safety for CB, CE, TUV, UL, FCC, and CCC
- Selective 100W ~ 500W power supply

Applications: For industrial computers, DVR/NVR, NAS, digital signages, ATM/Kiosk machines, firewall, networking and telecom products.

1U/2U



- Various 80 Plus (from Bronze to Platinum) certified efficiency
- Multiple selection for voltage output
- Unique active PFC (Power Factor Correction) circuit design
- Support OTP, OVP and OCP circuit protection
- Common safety for CB, CE, TUV, UL, FCC, and CCC
- Support PMBus v1.2

Applications: For industrial servers, storages, ATM/Kiosk machines, gaming machines, networking and telecom products.

About FSP Group

FSP Group is a leading manufacturer of power supply units.

Since established in 1993, the company has drawn together its R&D expertise, sizeable production capacity and outstanding product quality to consistently excel in this competitive marketplace.

FSP Group produces large selections of products to serve its OEM / ODM customers in LCD TV, LED Lighting, Medical, Industrial / Desktop computers and Servers. FSP Group has branch offices in more than 12 countries, 4 manufacturing facilities and about 8,500 people throughout the world.

With its broad range of products, FSP Group is uniquely positioned for strong growth on several long term trends and environment protection including green power products, higher energy-efficient conversion products, and highly electrical safety and reliable products.

FSP Group's global presence in Taiwan, Brazil, China, Germany, Hungary, India, Japan, Korea, Russia, UK, USA also provide our OEM / ODM customers with integrated global logistic. This translates to "Door-to-Door" service and faster time-to-market for product deliveries. Please check with your highly trained professional account manager on how to take advantage of our global logistic service for your business.

Our current focus in FSP Group is to further enhance our green power products, expand market presence of FSP branded retail products, and extend our research and development effort on all our products. At FSP Group, we are not only focusing on building a bigger company, also a better one.

Energetic | **Friendly** | **Simple** | **Reliable**

POWER
NEVER ENDS